



SERIES

OHD-FSP520W

52" Water Tight Sun Light Readable HDTV's



Features

Enclosure / Pedestal:

- All Weather
- All Aluminum Construction
- Mountable to optional movable base (As shown) or permanently to floor

Display:

- Solar Enhanced Daylight Viewable with Optional Optically Bonded Lens
- 52" Diagonal Active Matrix TFT LCD Displays
- Full High Definition 1080p Panels
- 178° / 178° wide viewing Angle
- 2000:1 Contrast Ratio
- 700 NITS Brightness
- On Screen Display (OSD) Monitor Controls with wireless remote

Video Inputs:

- HDMI, HD component, VGA, S-Video and Composite - Supports all Major Video Formats

Other Features:

- The OHD-FSP520W comes standard with T1 Cooling which boasts a wide operating temperature range from 32° - 122°F and a storage range of -4-140°F.
- Built in Audio amplifier

Options:

- Optional 42, 46, & 65" LCD Sizes
- Optional 4mm Lens with laminated IR filter and Optically Bonded for Daylight Readability
- Optional T2 Model with Heating (Operating range of -24°-122°F ambient temperature)
- Optional Base as shown

Please refer to our DSS line of products for other commercial products (LCD Sizes from 22"- 82") and more demanding temperature specifications.

Please feel free to consult with a Sales Engineer for additional information or visit our web site.

52" Free Standing Pedestal Welcome to Your New Entertainment Room!

OutdoorHDTV is the ultimate outdoor entertainment accessory. It is a High Definition, daylight viewable LCD monitor. It brings traditional indoor activities to the great outdoors. OutdoorHDTV brings High Definition right into your backyard and creates an entirely new entertainment room.

Soak in the hot tub while watching a romantic movie, watch the big game with your buddies while barbequing and not missing a minute of the action, enjoy family time as you relax under the stars while enjoying your OutdoorHDTV. The list is endless of the applications for the OutdoorHDTV.

OutdoorHDTV is the first commercial grade, all weather, High Definition 1080p daylight viewable LCD screen. Models include our Air Cooled T1 unit with an operating temperature range of 32°-122° F and our T2 model with an operating range of -24°-122°F with an integrated heater. The T2 option is for freezing temperature ranges and conditions. With this option, lower storage temperature ranges can also be achieved when the unit is left plugged in.

Please refer to our DSS line for our other commercial line of products to meet requirements that are more demanding.
DSS.DITHD.com

Standard Definition and High Definition input signals include: HDMI with Audio, HD/SD component (YPbPr, VGA, S-Video and composite).



OutdoorHDTV
1330 Specialty Dr, Suite A
Vista, CA, 92081
Phone 760.599.9225
Fax 760.454.0328

www.OutdoorHDTV.com
Sales@OutdoorHDTV.com







SERIES

OHD-FSP520W

Secure High Definition 52" LCD Water Tight Panel

<u>OHD-FSP520W:</u>	
<u>Display:</u>	
Display Type	FHD, Color TFT, 28 CCFL Backlight
Screen Diagonal	1321.8(52.04)
Aspect Ratio	16:9
Native Resolution	1920x1080
Display Colors	16.7M (8 Bit)
Brightness (Nits cd/m2)	700
Contrast Ratio	2000:1
Response Time (ms)	8ms
Surface Treatment	Hard Coat (3H) Anti Glare Treatment
Viewing Angle	89/89/89/89
<u>Video Controller:</u>	
Video Inputs and Ports	VGA, HDMI(2), YPbPr/YCbCr(2), S-Video, CVS, ATSC/NTSC Tuner, Full Featured RS232 Controllable Port, Audio In and Amplified Speakers Out
Video Input Resolutions and Format Supported	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
On Screen Adjustments	Full featured OSD Controls, IR Remote Control and RS-232 full-featured command set with discrete on/off, input select and volume control
Power Management	VESA Power Management
<u>Power:</u>	
Input Voltage	120V, 60HZ
Power Consumption	525W
<u>Misc:</u>	
Temp Operating (Deg C/F)	0 to +50 Deg C / 32 to 122 Deg F
Temp Storage (Deg C/F)	-20 to +60 Deg C / -4 to 140 Deg F
Weight (lbs)	230
Audio	-Input: Left and Right (RCA Jacks), PC 3.5mm Mini Earphone Jack -Output: 10-watt x 2 channels Speaker Terminals, Coaxial SPDIF Audio output



Optional Accessories:

OHD-FSPFCB	Movable Free Standing Pedestal Floor Circular Base	HDMI-C25	HDMI Cable - 25M
OHD-DCXX	OutdoorHDTV dust cover 22" - 65"	HDMI-C50	HDMI Cable - 50M
HDMI-TW10	HDMI over Ultra Wide Band Wireless (10M)	HDMI-C80	HDMI Cable - 80M
HDMI-TC100	HDMI over Single Coaxial (100M)	HDMI-CRC	HDMI Re Clocker
HDMI-TF300	HDMI over Fiber (300M)	LIR4420	4mm Lens with laminated IR filter and Optically Bonded for Day-light Readability
OHD - T2	Optional T2 for freezing temperature ranges and conditions. With this option, lower storage temperature ranges can be achieved when the unit is left plugged in.		